


## FL819ASC

<b>Lucida</b>	Ungalvanized
<b>Anima tessile</b>	Fiber core
<b>Crociata destra</b>	Right Regular Lay
<b>Crociata sinistra</b>	Left Regular Lay
<b>Resistenza 1370/1770 N/mm<sup>2</sup></b>	Tensile rope grade 1370/1770 N/mm <sup>2</sup>
<b>EN 12385-5</b>	EN 12385-5



8(9+9+1)S+FC  
152 fili/wires

Codice Code	Diametro funo Rope diameter  mm	Sezione metallica Metallic cross section  mm <sup>2</sup>	Diametro fili esterni Outer wires diameter  mm	Peso per metro Weight for meter  kg	Carico rottura minimo MBL	
					kN	kg
FL819ASD08	8	23,0	0,51	0,19	28,10	2865
FL819ASD09	9	29,0	0,57	0,25	35,60	3630
FL819ASD10	10	36,1	0,63	0,32	44,00	4487
FL819ASD11	11	43,5	0,69	0,41	53,20	5425
FL819ASD12	12	52,0	0,75	0,49	63,30	6455
FL819ASD13	13	61,0	0,82	0,57	74,30	7576
FL819ASD15	15	81,0	0,98	0,76	98,90	10085