


FX119K

Fune spiroidale compattata
Acciaio inossidabile AISI 316
Fune in accordo con EN 10264-4
Classe di resistenza 1570 N/mm²

Compact open spiral strand
Stainless Steel AISI 316
Rope according to EN 10264-4
Rope grade 1570 N/mm²



Codice Code	Fune Rope Ø mm	Formazione Construction	Peso Weight Kg/m	Carico di rottura minimo MBL	
				kN	Kg
FX119K02	2	1x7	0,020	4,10	418
FX119K025	2,5	1x7	0,030	6,80	693
FX119K03	3	1x7	0,050	9,80	999
FX119K035	3,5	1x7	0,070	13,30	1356
FX119K04	4	1x7	0,090	17,50	1785
FX119K05	5	1x19	0,140	25,50	2600
FX119K06	6	1x19	0,200	35,30	3600
FX119K07	7	1x19	0,270	49,00	4997
FX119K08	8	1x19	0,360	61,80	6302
FX119K10	10	1x19	0,570	98,00	9993
FX119K12	12	1x19	0,820	142,20	14500
FX119K14	14	1x25	1,160	189,30	19303
FX119K16	16	1x25	1,500	251,10	25605
FX119K19	19	1x31	2,060	313,90	32009