


FX636AC

Acciaio inossidabile AISI 316
Fune in accordo con EN 10264-4
Classe di resistenza 1570 N/mm²

Stainless Steel AISI 316
Rope according to EN 10264-4
Rope grade 1570 N/mm²



6x36WS+IWRC
265 fili/wires

Codice Code	Fune Rope Ø mm	Formazione Construction	Peso Weight Kg/m	Carico di rottura minimo MBL	
				kN	Kg
FX636A08	8	6x36WS+IWRC	0,260	35,70	3640
FX636A10	10	6x36WS+IWRC	0,400	55,90	5700
FX636A12	12	6x36WS+IWRC	0,590	80,50	8209
FX636A14	14	6x36WS+IWRC	0,800	110,00	11217
FX636A16	16	6x36WS+IWRC	1,050	143,00	14582
FX636A18	18	6x36WS+IWRC	1,330	181,00	18457
FX636A20	20	6x36WS+IWRC	1,640	224,00	22842
FX636A22	22	6x36WS+IWRC	1,980	271,00	27634
FX636A24	24	6x36WS+IWRC	2,360	322,00	32835
FX636A26	26	6x36WS+IWRC	2,760	354,00	36098
FX636A28	28	6x36WS+IWRC	3,210	410,00	41808
FX636A30	30	6x36WS+IWRC	3,680	471,00	48029