


Catene e accessori Winner Pro - Grado 12

Winner Pro chain and
accessory system in G12

Gancio autobloccante maggiorato a perno KLHGWP

KLHGWP Oversized self locking clevis hook



| Tipo Type | Portata WLL Kg | Dimensioni Dimensions | | | | | | | Peso Weight Kg |
|--------------|----------------------|--------------------------|---------|---------|---------|----------|---------|-------------|----------------------|
| | | a mm | b mm | d mm | e mm | g1 mm | h mm | s max mm | |
| KLHGWP 7 | 2360 | 21 | 107 | 9,5 | 130 | 48 | 27 | 1 | 1,10 |
| KLHGWP 8 | 3000 | 21 | 107 | 10,7 | 130 | 48 | 27 | 1 | 1,10 |
| KLHGWP 10 | 5000 | 26 | 137 | 14 | 166 | 61 | 35 | 1 | 2,16 |
| KLHGWP 13 | 8000 | 32 | 175 | 17,5 | 208 | 78 | 44 | 1,5 | 4,33 |
| KLHGWP 16 | 12500 | 37 | 195 | 21 | 237 | 86 | 54 | 2 | 7,70 |

- A new type of opening mechanism on the back of the hook makes unintentional opening absolutely impossible (Fig. 1 and 2).
- The hook offers very good protection against lateral displacement (Fig. 3).
- The extra-thick hook tip with milled groove prevents textile slings from slipping out (Fig. 3).
- Oversized hook opening.
- Deformed hooks can be easily detected by means of forged control marks (Fig. 4 and 5).
- Spare parts sets can be mounted quickly and easily without special tools.

- Un nuovo tipo di meccanismo di apertura sul retro del gancio rende assolutamente impossibile l'apertura involontaria (Fig. 1 e 2).
- Il gancio offre un'ottima protezione contro gli spostamenti laterali della chiusura di sicurezza (Fig. 3).
- La punta del gancio molto spessa con scanalatura fresata impedisce alle brache tessili di fuoriuscire (Fig. 3).
- Apertura del gancio maggiorata.
- I ganci deformati possono essere facilmente rilevati mediante segni di controllo forgiati (Fig. 4 e 5).
- Le parti di ricambio possono essere montate rapidamente e facilmente senza attrezzi speciali.




Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5