DISPOSITIVI BLOCCA CATENA PER PARANCHI A LEVA KL
CHAIN LOCK FOR KL LEVER HOISTS

The KITO KKSS Chain Locks are only intended for securing the Load Chain in conjunction with the KITO LB lever hoists in order to prevent slippage of the Load Chain on the non-Load Side. The KITO Chain Locks must be positioned as close as possible to the Lever Hoist Housing, max. 10 centimeters away from the Lever Hoist Housing.
Temperature Range for Use: -40° to + 60° Celsius.
Three models available:
- KKSS 60 for KL 80
- KKSS 80 for KL 160
- KKSS 100 for KL 320 - 630 - 900

I dispositivi blocca catena KITO KKSS sono destinati esclusivamente al fissaggio della catena di carico in combinazione con i paranchi a leva KITO KL al fine di impedire lo slittamento della catena dal lato opposto al carico. I dispositivi KITO devono essere posizionati il più vicino possibile al corpo del paranco a leva, max. 10 centimetri.
Intervallo di temperatura per l'uso: da -40° a + 60°.
Disponibili tre modelli:
- KKSS 60 per KL 80
- KKSS 80 per KL 160
- KKSS 100 per KL 320 - 630 - 900

NON INGAGGIATO
UNLOCKED

INGAGGIATO
Gli anelli di plastica devono essere visibili quando il dispositivo è ingaggiato

ENGAGED
The rubber rings must be visible in the locked position