

## Funi di acciaio a 6 trefoli


Steel wire ropes 6 strands

**ANIMA METALLICA**

STEEL CORE

### DRL 508 A COMPATTATA (lucida)

DRL 508 A COMPACTED STRANDS (ungalvanized)



#### 247 FILI

6xK31WS+IWRC  
anima metallica  
trefoli compattati  
crociata destra  
crociata sinistra

**Resistenza 1960 N/mm<sup>2</sup>**

#### 247 WIRES

6xK31WS+IWRC  
steel core  
compacted strands  
right regular lay  
left regular lay

**Tensile rope grade 1960 N/mm<sup>2</sup>**

Codice Code	Diametro funo Rope diameter mm	Diametro fili esterni Outer wires diameter mm	Peso per metro Weight for meter kg	Carico rottura minimo MBL	
				kN	kg
FLDRLK18	18	1,21	1,54	263,88	26916
FLDRLK20	20	1,35	1,90	325,78	33230
FLDRLK22	22	1,48	2,25	394,21	40210
FLDRLK24	24	1,62	2,71	469,18	47857
FLDRLK26	26	1,75	3,13	550,57	56158
FLDRLK28	28	1,89	3,70	638,61	65138
FLDRLK30	30	1,96	4,06	722,65	73711
FLDRLK32	32	2,04	4,72	830,00	84660