



COMPACT 9 SR COMPATTATA PARALLELA (zincata)

COMPACT 9 SR COMPACTED STRANDS LANG LAY (galvanized)

	Codice Code	Diametro fune Rope diameter	Diametro fili esterni Outer wires diameter	Peso per metro Weight for meter	Carico rottura minimo MBL	
		mm	mm	kg	kN	kg
 <p>112 FILI 9xK7+PWRC anima metallica trefoli compattati parallela destra parallela sinistra Resistenza 2160 N/mm²</p> <p>112 WIRES 9xK7+PWRC steel core compacted strands right lang lay left lang lay Tensile rope grade 2160 N/mm²</p>	FZC09SR06	6	0,50	0,15	32,00	3260
	FZC09SR07	7	0,58	0,21	44,30	4490
	FZC09SR08	8	0,67	0,27	57,10	5810
 <p>202 FILI 9xK17S+PWRC anima metallica trefoli compattati parallela destra parallela sinistra Resistenza 2160 N/mm²</p> <p>202 WIRES 9xK17S+PWRC steel core compacted strands right lang lay left lang lay Tensile rope grade 2160 N/mm²</p>	FZC09SR09	9	0,60	0,35	72,00	7300
	FZC09SR09,5	9,5	0,64	0,40	80,00	8160
	FZC09SR10	10	0,67	0,45	91,00	9290
	FZC09SR11	11	0,73	0,53	108,50	11070
	FZC09SR12	12	0,80	0,63	128,00	13060
	FZC09SR13	13	0,87	0,75	152,00	15500
	FZC09SR14	14	0,95	0,87	174,00	17750
	FZC09SR16	16	1,08	1,14	227,30	23190

