

Codice Code	Portata WLL	Dimensioni Dimensions											Peso Weight	
		t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm		k mm
P 6036														
AGRLVD120	120	95	95	215	91	147	400	238	647	440	428	50	110	
AGRLVD150	150	105	108	245	102	169	410	275	688	490	485	60	160	
AGRLVD200	200	120	130	288	113	179	513	290	838	520	530	60	235	
AGRLVD250	250	130	140	308	118	205	554	305	904	560	565	65	285	
AGRLVD300	300	140	150	335	123	205	618	305	996	575	585	70	340	
AGRLVD400	400	170	175	387	164	231	668	325	1114	690	665	70	560	
AGRLVD500	500	180	185	410	1364	256	718	350	1190	720	710	70	685	
AGRLVD600	600	200	205	458	189	282	718	375	1243	810	775	70	880	
AGRLVD700	700	210	215	468	204	308	718	400	1263	870	820	70	980	
AGRLVD800	800	210	220	478	204	308	718	400	1270	870	820	70	1100	
AGRLVD900	900	220	230	500	215	328	718	420	1296	920	860	70	1280	
AGRLVD1000	1000	240	240	530	215	349	718	420	1336	940	900	70	1460	
AGRLVD1250	1250	260	270	600	230	369	768	450	1456	1025	970	70	1990	
AGRLVD1500	1500	280	290	640	230	369	818	450	1556	1025	1010	70	2400	

- Coefficiente di sicurezza 5.
- Temperatura di lavoro: da 120 t a 600 t: -40°C ÷ 200°C.
da 700 t a 1500 t: -0°C ÷ 200°C.
- Safety factor 5.
- Temperature range: from 120 t to 600 t: -40°C ÷ 200°C.
from 700 t to 1500 t: -0°C ÷ 200°C.

Tipo P 6036

Con dado e coppiglia
Acciaio alta resistenza gr. 8
Finitura: verniciati

P 6036 Type

With safety bolt
Gr. 8 high tensile steel
Finish: painted

