



Tipo AUBL G 6413
Acciaio alta resistenza
Finitura: zincatura a caldo

AUBL G 6413 type
High tensile steel
Finish: hot dipped galvanized



Codice Code	Fune Rope		Carico di rottura capocorda Socket MBL t	Dimensioni Dimensions							Peso Weight Kg
	Ø mm	Ø inch		A mm	B mm	C mm	D mm	E mm	F mm	G mm	
AAUBL08	7-8	5/16	8	128	110	51	18	16	9	36	0,8
AAUBL10	9-10	3/8	12	165	142	62	20,5	21	11	46	1,5
AAUBL13	11-13	1/2	20	175	146	66	25	25	12	57	2,4
AAUBL16	14-16	5/8	25	211	176	82	31	30	15	70	4
AAUBL19	18-19	3/4	40	252	212	95	38	35	16	80	7,4
AAUBL22	20-22	7/8	55	288	240	110	44	41	19	95	11
AAUBL26	24-26	1	75	329	274	130	51	51	22	110	16
AAUBL28	27-29	1 1/8	90	375	310	144	57	57	25	130	22
AAUBL32	30-32	1 1/4	110	423	350	155	63	64	28	146	31
AAUBL35	34-36	1 3/8	125	474	400	163	69	64	28	148	39
AAUBL38	37-39	1 1/2	150	527	450	178	76	70	30	153	48
AAUBL42	40-42	1 5/8	170	580	500	187	76	76	33	160	64
AAUBL46	43-48	1 3/4-1 7/8	225	650	550	226	89	89	39	186	96
AAUBL50	49-52	2	280	745	640	240	101	95	46	194	130
AAUBL56	54-58	2 1/4	360	785	660	275	114	108	54	230	180

- In accordo a EN 13411-6.
- Su richiesta con dado e coppiglia.
- According to EN 13411-6.
- Upon demand with safety bolt.

Tolleranze sulle dimensioni: ± 5%
Tolerances on dimensions: ± 5%