

Forche per pallets

Pallet hooks

Tipo RPHA con bilanciamento automatico

RPHA type pallet hooks with automatic balancing

- Pallet hooks with automatic balancing device.
- The suspension ring is moved automatically by a spring and it is always aligned with the center of gravity of the load.
- A safety chain is supplied as standard. Moreover the blades incline upwards avoiding accidental slipping of the load.
- Easy height and loading forks adjustment to comply with the dimension of the load.
- It is also possible to lift rings and coils by closing the loading forks.

A minimum load 25% of total safe capacity is required for activating the automatic balancing of the load.

Attention: the load must have a stable center of gravity, aligned as much as possible with the suspension point. The forks are not suitable for bulky non-barycentric loads, and in particular in the case of liquid loads. The liquid moves making balancing impossible.

- Forche con dispositivo di bilanciamento automatico del carico.
- L'anello di sospensione si sposta automaticamente per mezzo di una molla ed è sempre allineato con il baricentro del carico.
- Le forche vengono consegnate con una catena per imbracare il carico. Inoltre le pale si inclinano verso l'alto quando la forca viene sollevata, escludendo lo scivolamento accidentale del carico.
- Facile regolazione dell'altezza della forca e delle pale per adeguarsi alle dimensioni del carico e del pallet. Avvicinando completamente le pale è possibile trasportare anche anelli o coils.

La funzione di bilanciamento automatico richiede un carico minimo pari al 25% della portata nominale della forca.

Attenzione: il carico applicato deve avere un baricentro stabile, il più possibile in asse con il punto di sospensione. Le forche non sono idonee per carichi voluminosi non baricentrici, e, in particolare nel caso di carichi liquidi. Il liquido si sposta rendendo impossibile il bilanciamento.

Tipo Type	Portata WLL t	Peso Weight Kg	Dimensioni Dimensions					
			a mm	b mm	d mm	h mm	h1 mm	L mm
RPHA - 1	1	140	100x80	350-900	100x30	1300-2000	1600-2300	1000
RPHA - 2	2	220	100x80	400-900	120x40	1300-2000	1655-2355	1000
RPHA - 3	3	280	120x100	450-900	120x50	1300-2000	1720-2420	1000
RPHA - 5	5	380	136x120	530-1000	150x60	1300-2000	1710-2410	1000

