

**ARRIDATOIO ASTA-FORCELLA SNODATA**  
TOGGLE-SWAGE TURNBUCKLES

- Acciaio inossidabile AISI 316.
- Corpo in bronzo cromato ad alta resistenza.
- Stainless steel AISI 316.
- Chrome plated high grade brass body.

Fune Rope  Ø mm	Filettatura Thread  Pollici UNF UNF inches G	Codice Code	Perno Pin  mm	Dimensioni Dimensions				Carico di rottura minimo MBL  Kg	Peso Weight  g
				L1 mm	L2 mm	L4 mm	A mm		
3	1/4"	AN330306A	6,35	255	193	17	8	1300	127
4	1/4"	AN330406A	6,35	265	203	17	8	1300	130
4	5/16"	AN330408A	8,0	304	228	20	10	1700	174
5	5/16"	AN330508A	8,0	310	234	20	10	2200	185
5	3/8"	AN330510A	9,5	349	265	26	12	2400	282
6	3/8"	AN330610A	9,5	364	280	26	12	3400	325
6	7/16"	AN330611AX	11,0	397	307	28	15	4600	475
7	7/16"	AN330711AX	11,0	408	318	28	15	4600	475
6	1/2"	AN330612AX	12,7	425	319	35	18	5400	740
7	1/2"	AN330712AX	12,7	433	327	35	18	6100	770
8	1/2"	AN330812AX	12,7	448	342	35	18	6100	820
8	5/8"	AN330816AX	16,0	536	404	41	20	8700	1260
10	5/8"	AN331016AX	16,0	545	413	41	20	9700	1350
10	3/4"	AN331020AX	19,0	625	465	45	24	9700	1900
12	3/4"	AN331220AXX*	19,0	660	500	45	24	14000	2000
12	7/8"	AN331222AX*	22,0	786	592	49	26	14000	3110
14	7/8"	AN331422AX	22,0	794	600	49	26	15900	3090
14	1"	AN331425AX	25,4	932	692	59	29	15900	5120
16	1"	AN331625AX	25,4	940	700	59	29	19400	5050
19	1 1/8"	AN331927AX	28,0	1034	790	62	34	27600	8579
22	1 1/4"	AN332230AX	32,0	1153	877	69	40	34600	11865
26	1 3/8"	AN332636AX	35,0	1296	990	81	44	42400	16139
28	1 5/8"	AN332842A	40,0	1554	1178	99	48	59700	24613

\* Terminale OD = 21,4 mm

\* OD terminal = 21,4 mm

