

**ARRIDATOIO ASTA-FORCELLA FISSA SALDATA**  
FORK-SWAGE TURNBUCKLE

- Forcella saldata.
- Canaula chiusa.
- Acciaio inossidabile AISI 316 elettropulito.
- Welded fork.
- Closed body.
- Polished Stainless Steel AISI 316.

Codice Code	Filettatura Thread G	Fune Rope Ø mm	Perno Pin	Dimensioni Dimensions					Carico di rottura minimo MBL kg	Peso Weight Kg
				A mm	B mm	D mm	L1 mm	L2 mm		
AN120205	M5	2,0	5,0	7,5	9,4	5,5	206	152	800	0,05
AN122505	M5	2,5	5,0	7,5	9,4	5,5	206	152	800	0,05
AN120306	M6	3,0	5,0	7,5	9,4	6,4	232	170	1.200	0,09
AN120406	M6	4,0	5,0	7,5	10,4	7,5	242	180	1.200	0,09
AN120408	M8	4,0	6,0	9,5	10,4	7,5	275	199	1.600	0,13
AN120508	M8	5,0	6,0	9,5	13,0	9,0	281	205	1.600	0,13
AN120510	M10	5,0	8,0	11,0	14,0	9,0	312	228	2.500	0,23
AN120610	M10	6,0	8,0	11,0	15,0	12,6	327	243	3.200	0,26
AN120612	M12	6,0	12,0	14,0	18,5	12,6	393	287	5.100	0,48
AN120712	M12	7,0	12,0	14,0	25,0	14,2	401	295	5.100	0,50
AN120812	M12	8,0	12,0	14,0	25,0	16,0	416	310	5.100	0,54
AN120714	M14	7,0	12,0	14,0	25,0	14,2	439	319	6.800	0,58
AN120814	M14	8,0	12,0	14,0	25,0	16,0	453	333	6.800	0,64
AN120816	M16	8,0	14,0	18,0	32,0	16,0	498	365	8.700	0,90
AN121016	M16	10,0	14,0	18,0	33,0	17,8	506	373	9.400	0,93
AN121020	M20	10,0	19,0	24,0	38,3	17,8	587	427	9.700	1,70
AN121220*	M20	12,0	19,0	24,0	38,3	20,0	606	446	11.400	1,70
AN121422*	M22	14,0	22,0	30,0	46,0	25,0	736	555	15.900	4,52
AN121622*	M22	16,0	22,0	30,0	57,5	28,0	696	588	18.000	4,90
AN121424*	M24	14,0	25,4	30,0	47,8	25,0	846	613	15.900	6,42
AN121624*	M24	16,0	25,4	30,0	47,8	28,0	874	641	19.400	6,62
AN121927*	M27	19,0	28,0	32,0	68,0	34,5	968	734	23.000	8,78
AN122230*	M30	22,0	32,0	35,0	76,0	40,5	1076	814	28.000	10,74
AN122636*	M36	26,0	35,0	40,0	86,0	46,0	1195	921	41.000	16,82

\* Disponibili con canaula in acciaio inossidabile ed inserto in bronzo (su richiesta)

\* Available with threaded Bronze inserts in a S/S Body (on request)

