

ARRIDATOIO ASTA-FORCELLA FRESATA
MACHINED FORK-SWAGE TURNBUCKLE

- Forcella fresata.
- Canala chiusa.
- Acciaio inossidabile AISI 316 elettropulito.
- Machined fork.
- Closed body.
- Polished Stainless Steel AISI 316.

Codice Code	Filettatura Thread G	Fune Rope Ø mm	Perno Pin	Dimensioni Dimensions					Carico di rottura minimo MBL kg	Peso Weight Kg
				A mm	B mm	D mm	L1 mm	L2 mm		
AN741220	M20	12	19	20	45	20,0	646	492	11.400	2,4
AN741422	M22	14	22	22	49	25,0	720	540	15.000	6,5
AN741622	M22	16	22	22	49	28,0	745	565	15.000	6,7
AN741624	M24	16	25	25	52	28,0	863	630	18.000	8,8
AN741927	M27	19	28	30	55	34,5	963	728	23.000	13,3
AN742230	M30	22	32	35	67	40,5	1082	820	28.000	18,9
AN742636	M36	26	35	35	67	46,0	1186	912	41.000	24,8
AN742642	M42	28	40	34	75	50,0	1298	992	70.000	23,3
AN742648	M48	32	45	38	91	58,0	1461	1131	90.000	32,1
AN742652	M52	36	50	49	100	65,0	1628	1258	110.000	43,0

* Materiale 1.4462 (SAF 2205)
* Material 1.4462 (SAF 2205)

