

**ARRIDATOIO FORCELLA-FORCELLA FISSA SALDATA**  
FORK-FORK TURNBUCKLE

- Forcelle saldate.
- Canala chiusa.
- Acciaio inossidabile AISI 316 elettropulito.
- Welded forks.
- Closed body.
- Polished Stainless Steel AISI 316.

Codice Code	Filettatura Thread G	Perno Pin	Dimensioni Dimensions				Carico di rottura minimo MBL kg	Peso Weight kg
			A mm	B mm	L1 mm	L2 mm		
AN120005	M5	5	7,5	12	180	126	800	0,5
AN120006	M6	5	7,5	12	200	138	1.000	0,9
AN120008	M8	6	9,5	13	234	158	1.600	1,4
AN120010	M10	8	11,0	15	272	188	3.200	2,4
AN120012	M12	12	14,0	25	350	244	5.100	5,3
AN120014	M14	12	14,0	25	387	267	6.900	6,4
AN120016	M16	14	18,0	32	446	313	9.400	10,0
AN120020*	M20	19	24,0	48	550	390	14.000	19,7
AN120022*	M22	22	30,0	57	653	472	18.000	44,8
AN120024*	M24	25	30,0	62	769	536	21.000	63,8
AN120027*	M27	28	32,0	68	825	590	23.000	88,1
AN120030*	M30	32	35,0	76	907	647	28.000	106,0
AN120036*	M36	35	40,0	86	990	715	41.000	165,7

- Nota: Tutti i carichi di rottura sono calcolati sui perni
- \* Disponibili con canala in acciaio inossidabile ed inserto in bronzo (su richiesta)
- Note: All breakloads are determined by clevis pin and thread
- \* Available with threaded Bronze inserts in a S/S Body (on request)

