

ARRIDATOIO ASTA-FORCELLA SNODATA APEX CANAULA CHIUSA
APEX TOGGLE-SWAGE TURNBUCKLES OPEN BODY

- Acciaio inossidabile AISI 316.
- Corpo in inossidabile AISI 316 con inserti filettati in bronzo.
- Stainless steel AISI 316.
- Stainless steel AISI 316 body with bronze threaded inserts.

Fune Rope Ø mm	Filettatura Thread Pollici UNF UNF inches G	Codice Code	Perno Pin mm	Dimensioni Dimensions				Carico di rottura minimo MBL Kg	Peso Weight g
				L1 mm	L2 mm	L4 mm	A mm		
5	3/8"	AN240510AS	6,35	355	273	17	8	1300	127
6	3/8"	AN240610AS	6,35	370	288	17	8	1300	130
6	7/16"	AN240611AXS	8,0	403	315	20	10	1700	174
7	7/16"	AN240711AXS	8,0	414	326	20	10	2200	185
7	1/2"	AN240712AXS	9,5	427	328	26	12	2400	282
8	1/2"	AN240812AXS	9,5	442	343	26	12	3400	325
8	5/8"	AN240816AXS	11,0	537	412	28	15	4600	475
10	5/8"	AN241016AXS	11,0	546	421	28	15	4600	475
10	3/4"	AN241020AXS	12,7	651	491	35	18	5400	740
12	3/4" - BS 21,4	AN241220AXXS	12,7	686	526	35	18	6100	820
14	7/8"	AN241222AXS	16,0	788	600	41	20	8700	1260
16	1"	AN241625AXS	16,0	942	708	41	20	9700	1350
19	1 1/8"	AN241927AXS	19,0	1035	798	45	24	9700	1900
22	1 1/4"	AN242230AXS	19,0	1147	879	45	24	14000	2000
26	1 3/8"	AN242636AXS	22,0	1298	991	49	26	14000	3110

