

TERMINALE A PRESSARE CON FORCELLA SALDATA
SWAGE FORK

- Acciaio inossidabile
AISI 316.
- Stainless steel AISI 316.

Fune Rope mm	Codice Code	Perno Pin D mm	Dimensioni Dimensions					Carico di rottura minimo MBL Kg	Peso Weight Kg
			L1 mm	L2 mm	L3 mm	D1 mm	A mm		
3,0	AN100503	5,0	67	12	38	6,35	7,5	800	0,02
3,0	AN100603	6,0	68	13	38	6,35	9,5	1300	0,03
4,0	AN100504	5,0	71	12	45	7,50	7,5	800	0,03
4,0	AN100604	6,0	73	13	45	7,50	9,5	1500	0,03
4,0	AN100804	8,0	77	15	45	7,50	11,0	1700	0,05
5,0	AN100605	6,0	83	13	51	9,00	9,5	1500	0,04
5,0	AN100805	8,0	87	15	51	9,00	11,0	2400	0,06
6,0	AN100806	8,0	99	15	64	12,58	11,0	3200	0,10
6,0	AN109506	9,5	104	19	64	12,58	12,0	3800	0,11
6,0	AN101206	12,0	110	25	64	12,58	14,0	5200	0,18
7,0	AN101207	12,0	119	25	70	14,20	14,0	6500	0,18
8,0	AN101208	12,0	136	25	83	16,00	14,0	6500	0,22
8,0	AN101608	16,0	145	33	83	16,00	18,0	8500	0,26
10,0	AN101410	14,0	151	33	89	17,80	18,0	9400	0,35
12,0	AN101612	16,0	174	33	105	20,00	18,0	11200	0,60
12,0	AN101912	19,0	189	52	105	20,00	24,0	11200	0,66
14,0	AN102514	25,0	235	62	140	25,00	30,0	15000	1,25
16,0	AN102516	25,0	264	62	160	28,00	30,0	19000	1,40

