

ASTA FILETTATA UNF
THREAD TERMINALS UNF

- Acciaio inossidabile
AISI 316.
- Stainless steel AISI 316.

Fune Rope	Filettatura Thread	Codice Code		Dimensioni Dimensions				Carico di rottura minimo MBL	Peso Weight
		Filettatura destra Right thread	Filettatura sinistra Left thread	D1 mm	L1 mm	L2 mm	L3 mm		
3,0	1/4"	930306A	940306A	6,35	100	48	38	1300	0,02
4,0	1/4"	930406A	940406A	7,5	110	48	45	1300	0,03
4,0	5/16"	930408A	940408A	7,5	117	57	45	1700	0,04
5,0	5/16"	930508A	940508A	9,0	123	57	51	2200	0,04
5,0	3/8"	930510A	940510A	9,0	130	63	51	2400	0,05
6,0	3/8"	930610A	940610A	12,58	145	63	64	3400	0,08
6,0	7/16"	930611A	940611A	12,58	157	68	64	4600	0,10
7,0	7/16"	930711A	940711A	14,2	162	68	70	4600	0,13
6,0	1/2"	930612A	940612A	12,58	162	80	64	5400	0,11
7,0	1/2"	930712A	940712A	14,2	170	80	70	6100	0,14
8,0	1/2"	930812A	940812A	16,0	185	80	83	6100	0,19
8,0	5/8"	930816A	940816A	16,0	203	100	83	8700	0,26
10,0	5/8"	931016A	941016A	17,8	212	100	89	9700	0,30
10,0	3/4"	931020A	941020A	17,8	230	120	89	9700	0,39
12,0	3/4"	* 931220AX	941220AX	21,4	265	120	120	14200	0,49
14,0	7/8"	931422A	941422A	25,0	308	140	140	15900	0,79
16,0	1"	931625A	941625A	28,0	363	170	160	19400	1,26
19,0	1-1/8"	931927A	941927A	34,5	425	180	200	27600	2,10
22,0	1-1/4"	932230A	942230A	40,5	480	200	230	34600	3,13
26,0	1-3/8"	932636A	942636A	46,0	550	220	280	42400	4,70
28,0	1-5/8"	932842A	942842A	50,0	639	270	300	64000	6,82

* Terminale OD = 21,4 mm
* OD terminal = 21,4 mm

